

**DECLARATION OF PERFORMANCE**  
**№ K93-02-DEP-0001**

**In accordance with Annex III of Regulation (EU) № 305/2011**

Product name:**MORTAR FOR EXTERIOR INSULATION**  
**“INDOM THERMO UNIVERSAL”**

1. Type of product unique identification code:

2. Type, batch and serial number or other element which allows the construction product to be identified under the requirements of Art. 11 Para. 4:

**MORTAR FOR EXTERIOR INSULATION “INDOM THERMO**  
**UNIVERSAL”**

**Batch №1/25.06.2014**

3. Intended use or uses of the construction product in accordance with the applicable Harmonized technical specification, as provided by the manufacturer:

**Adhesive for bonding and reinforcement of external thermal insulation**

4. Name, registered trade name or registered trademark and contact address off the manufacturer, the requirements of Art. 11 Para. 4:

**INDOM Bulgaria Ltd, 4000 Plovdiv, Bulgaria, tel.:+30.211.8502737**

5. When applicable, name and contact address of the authorized representative whose authorization includes the tasks referred to in Art. 12 Para. 2:

**Not applicable**

6. System or systems for assessment and verification of constancy of performance of the construction product, in cases when they are set out in Construction Products Regulation (CPR) Annex V:

**System 3**

7. In case of Declaration of performance regarding the construction product covered by the harmonized technical specification standard:

The notified laboratory of **Building research institute ("NISI" EOOD)**, NB 2032, has carried out type testing under system 3 and has issued an Initial testing report with № ITT-08.11/22.05.2008.

8. In case of Declaration of performance regarding a construction product for which a European Technical Assessment is issued:

**Not applicable**

9. Declared performance parameters:

Essential characteristics	Performance parameters	Harmonized technical specification
Open time according to EN 346:2002	40 min.	EN 12004:2007 +A1:2012
Adhesive strength under tension on oblique surface, according to EN 1348:2001	5,50 ± 0,50 N/mm <sup>2</sup>	
Compressive strength according to EN 1015-11	15,00 ± 1,00 N/mm <sup>2</sup>	
Container Open Time	>6 hrs	
Sliding	<0,5 mm	
Adhesion to XPS for 28 days	0,35 N/mm <sup>2</sup>	
Adhesion to EPS for 28 days	0,1 N/mm <sup>2</sup>	

10. The performance parameters of the product, described in point 1 and point 2, are in accordance with the declared performance characteristics in point 9. The present Declaration of performance is issued under the sole responsibility of the manufacturer mentioned in point 4.

Signed by and on behalf of manufacturer by:  
City of Plovdiv, 25.06.2014

Aris Kontopulos  
Manager: *signature:illegible*

*Round stamp of INDOM Bulgaria*

The undersigned Teodora Kirilova Yoncheva with my signature placed below certify that the translation I have made from Bulgarian language to English language of the attached document – Declaration of Performance №K93-02-DEP-0001 - is true to the original. The translation consists of 2 (two) pages.

Translator:

*Teodora Kirilova Yoncheva*  
